

# PROCESS ANTIFOAM

## *Industrial Process Antifoam*

- Antifoam emulsion designed for defoaming aqueous solutions
- Readily dispersible with mild agitation
- Ready to use liquid formula

### General Description

**Process Antifoam** is an emulsion of polydimethylsiloxane designed for defoaming aqueous systems. **Process Antifoam** is easily dispersed and is used effectively in a variety of water-based industrial processes and products.

**Spectrum®** treatment products and programs are the key to long-term preventive maintenance. Make **Spectrum®** a part of your preventive maintenance program today.

### Specifications

Wt/Gallon:	8.205 lbs
pH:	7.5
Specific Gravity:	0.984 – 1.0
Appearance:	White Viscous Liquid
Heat Stability:	110°F

### Handling

Recommended storage limit is 6 months.

Keep container closed when not in use.

As with most emulsions, storage in a cool place (60 – 75°F max.) in tightly closed containers will provide maximum shelf life.

### Application

The amount of **Silicone Process Antifoam** required will vary depending on operating conditions. Dosage rate will be from 3 ounces to 25 ounces per 1000 gallons system capacity.

Industrial Water Treatment By:



ALLIANCE GROUP, INC.  
GERMANTOWN, WI 53022

S  
P  
E  
C  
T  
R  
U  
M®